

RESIDENTIAL & COMMERCIAL

Chimney and Fireplace Application

Permit Number F/p _____

Map/Lot _____

Permit Fee _____

Date Received _____

Date Issued _____

Number of flues: _____

Location of Construction: _____

Description of work and brief description of materials to be used: _____

Consumer Information

Property owner: _____

Address: _____

Phone: _____

Cell Phone: _____

Installer Information

Contractor: _____

Phone: _____

Address: _____

Cell Phone: _____

Fax: _____

Appliance Information Fuel type: Wood ___ Gas ___ Oil ___ Other ___

Describe other: _____

Construction standards will be per NFPA 211, 2003 Edition

Combustion air ducts ARE required by the AHJ and will be installed per section 11.5 of NFPA 211, 2003 Edition (see attached)

A disclosure per 32MRSA chapter 33 section 2313-A is required to be provided to the consumer prior to installation taking place.

Inspections are required: When the damper is in place and throat is complete. Failure to schedule inspections and receiving final approval by the Inspector will delay the Certificate of Occupancy. Fines will be imposed at a rate not less than One Hundred Dollars (\$100.00) per day, nor more than Twenty-five Hundred Dollars (\$2,500.00) per day.

Signature of Property Owner, or Mason Contractor: _____ Date: _____

Please Print: _____

NFPA 211, 2003 Edition

11.5 Combustion Air Ducts.

11.5.1 Where required by the AHJ, combustion air ducts shall be installed in accordance with this section.

11.5.1.1 Combustion air ducts for factory-built fireplaces shall be a listed component of the fireplace and shall be installed according to the manufacturer's instructions.

11.5.1.2 Listed combustion air duct systems for masonry fireplaces shall be installed according to the terms of their listing and the manufacturer's instructions.

11.5.2 Combustion air ducts shall extend as directly as practicable from the outdoors (inlet) to a termination outside the fire chamber (outlet).

11.5.3 Combustion air ducts shall be constructed of one of the following:

- (1) Masonry
- (2) Galvanized steel with a thickness not less than 26 gauge [0.019 in. (0.483 mm)]
- (3) Other approved noncombustible material

11.5.3.1 Combustion air ducts shall be equipped with a damper that is capable of being fully closed.

11.5.4 Combustion air ducts that terminate outside the fire chamber but within 6 in. (152 mm) of the fire chamber shall be designed and installed to prevent the direct entry of flame, embers, or ashes from the fire chamber into the duct.

11.5.5 Unlisted combustion air ducts shall be installed with a minimum 1-in. (25.4-mm) clearance to combustibles for all parts of the duct construction within 5 ft (1.5 m) of the duct outlet.

11.5.6 The exterior inlet of the combustion air duct shall be screened.

11.5.7 Combustion air ducts shall not originate in any of the following:

- (1) An attic
- (2) A basement
- (3) A garage
- (4) Another interior space